



CP9122BR - Lightweight & easy handling

Benefits

- ▶ General maintenance applications
- ▶ Lightweight but rugged housing
- ▶ Durability and performance

Features

- ▶ Keyless adjustable protective guard
- ▶ Aluminum alloy housing
- ▶ Helical bevel gear design
- ▶ 4-1/2" (115 mm) wheel capacity
- ▶ 5/8"-11 spindle thread
- ▶ 0.8 hp (600 W) governed motor
- ▶ Ergonomic side handle

Technical description		
Part number	6151957222	
Model	CP9122BR	
Spindle thread	5/8-11	
Wheel size	115 mm	4.5"
Cup wheel Diam.	-	-
Free speed	12000 rpm	
Power	600 W	0.8 hp
Length	233 mm	9.3"
Net weight	1.9 kg	4.18 lb
Front exhaust	Front exhaust	
Sound pressure	84 db(A)	
Sound Power	95 db(A)	
Vibration (ISO-8662-4)	<2.5 m/s ²	
Vibration α (ISO-28927-1)	8.6 m/s ²	
Vibration K (ISO-28927-1)	4.6 m/s ²	
Average air consumption	7 l/s	14.84 cfm
Average air consumption	420 l/mn	14.84 cfm
Actual air consumption	14 l/s	29.68 cfm
Actual air consumption	840 l/mn	29.68 cfm
Free speed air consumption	9.9 l/s	21 cfm
Min. hose size	10 mm	3/8"
Air inlet thread size	1/4	