# **Safety Data Sheet**

Issue Date: 19-DEC-2022 Revision Date: 19-DEC-2022 Version 1

## 1. IDENTIFICATION

<u>Product identifier</u>

**Product Name** 

LINER SEALER

Other means of identification

SDS#

**BPN-008** 

Product Code UN/ID No Catalog Numbers: : 93-751, 93-752, 93-754, 93-755

UN1133

Recommended use of the chemical and restrictions on use

Recommended Use

Rubber adhesive.

Details of the supplier of the safety data sheet

Supplier Address BESTPATCH North America 444 E. North Street Morristown, IN 46161 765-763-7777

Emergency telephone number

**Emergency Telephone** 

INFOTRAC 1-352-323-3500 (International) 1-800-535-5053 (North America)

## 2. HAZARDS IDENTIFICATION

Appearance Black high viscosity liquid

Physical state Liquid

Odor Petrolic

#### Classification

Skin corrosion/irritation	Category 2	
Specific target organ toxicity (single exposure)	Category 3	
Aspiration toxicity	Category 1	
Flammable liquids	Category 2	

## Signal Word

Danger

## Hazard statements

Causes skin irritation
May cause drowsiness or dizziness
May be fatal if swallowed and enters airways
Highly flammable liquid and vapor



## Precautionary Statements - Prevention

BPN-008 - LINER SEALER Revision Date: 19-DEC-2022

Wash face, hands and any exposed skin thoroughly after handling

Wear protective gloves/protective clothing/eye protection/face protection

Avoid breathing dust/fume/gas/mist/vapors/spray Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. — No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof equipment Use only non-sparking tools

Take precautionary measures against static discharge

Keep cool

Precautionary Statements - Response

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

Wash contaminated clothing before reuse

If skin irritation occurs: Get medical advice/attention

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a poison center or doctor/physician if you feel unwell

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

In case of fire: Use CO2, dry chemical, or foam for extinction

#### Precautionary Statements - Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

#### Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

## Other hazards

Very toxic to aquatic life with long lasting effects

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No	Weight-%
N-Heptane	142-82-5	80-90

<sup>\*\*</sup>If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.\*\*

## 4. FIRST AID MEASURES

## Description of first aid measures

General Advice

Provide this SDS to medical personnel for treatment.

**Eye Contact** 

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

**Skin Contact** 

Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing

before reuse.

**Inhalation** 

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a

poison center or doctor/physician if you feel unwell. If not breathing, give artificial

respiration,

Ingestion

Do NOT induce vomiting, Immediately call a poison center or doctor/physician. If yomiting

occurs naturally, have victim lean forward to reduce risk of aspiration.

BPN-008 - LINER SEALER Revision Date: 19-DEC-2022

## Most important symptoms and effects, both acute and delayed

**Symptoms** 

Causes skin irritation. May cause drowsiness or dizziness. May be harmful in contact with skin. May cause pulmonary edema. Possible symptoms are irritation of the mucous membranes, dry cough and respiratory difficulty. Other symptoms may include dizziness, headache, nausea, and loss of coordination.

## Indication of any immediate medical attention and special treatment needed

Notes to Physician

Treat symptomatically. Aspiration of material into the lungs due to vomiting can cause chemical pneumonitis which can be fatal. Epinephrine and other sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to high concentrations of hydrocarbon solvents. The use of other drugs with less arrhythmogenic potential should be considered. If sympathomimetic drugs are administered, observe for the development of cardiac arrhythmias.

## **5. FIRE-FIGHTING MEASURES**

Suitable Extinguishing Media

Water spray (fog). Alcohol resistant foam. Dry chemical. Carbon dioxide (CO2).

Unsuitable Extinguishing Media Do not use solid water streams.

Specific Hazards Arising from the Chemical

Highly flammable liquid and vapor. The liquid vapor may settle into low areas or may travel along the ground or surface to ignition sources where they might ignite or explode. Flash back possible over considerable distance.

Hazardous combustion products Carbon monoxide. Carbon dioxide (CO2).

Explosion Data

Sensitivity to Static Discharge Take precautionary measures against static discharge.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use water spray to keep fire-exposed containers cool. Fight fire remotely due to the risk of explosion.

## 6. ACCIDENTAL RELEASE MEASURES

## Personal precautions, protective equipment and emergency procedures

**Personal Precautions** 

Wear protective clothing as described in Section 8 of this safety data sheet. Evacuate personnel to safe areas. Remove all sources of ignition. Ensure adequate ventilation. Avoid breathing vapors or mists.

## Environmental precautions

**Environmental precautions** 

Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information.

#### Methods and material for containment and cleaning up

**Methods for Containment** 

Prevent further leakage or spillage if safe to do so. Prevent evaporation by covering with foam. Soak up and contain spill with an inert (i.e. vermiculite, dry sand or earth) absorbent material.

Methods for Clean-Up

Use only non-sparking tools. Place in properly labeled, sealed, non-leaking containers. Dispose of contents/container via a licensed waste disposal contractor. For waste disposal, see section 13 of the SDS.

Revision Date: 19-DEC-2022

## 7. HANDLING AND STORAGE

#### Precautions for safe handling

Advice on Safe Handling

Wash face, hands and any exposed skin thoroughly after handling. Wear protective

gloves/protective clothing and eye/face protection. Avoid breathing

dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area, Keep away from heat/sparks/open flames/hot surfaces. — No smoking, Ground/bond container and receiving equipment. Use spark-proof tools and explosion-proof equipment. Take

precautionary measures against static discharges. Keep cool.

## Conditions for safe storage, including any incompatibilities

**Storage Conditions** 

Keep containers tightly closed in a cool, well-ventilated place. Store locked up. Heat

sensitive-store under inert gas.

Incompatible Materials

Strong oxidizing agents.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### **Exposure Guidelines**

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
N-Heptane 142-82-5	STEL: 500 ppm TWA: 400 ppm	TWA: 500 ppm TWA: 2000 mg/m³ (vacated) TWA: 400 ppm (vacated) TWA: 1600 mg/m³ (vacated) STEL: 500 ppm (vacated) STEL: 2000 mg/m³	IDLH: 750 ppm Ceiling: 440 ppm 15 min Ceiling: 1800 mg/m³ 15 min TWA: 85 ppm TWA: 350 mg/m³

## Appropriate engineering controls

**Engineering Controls** 

Apply technical measures to comply with the occupational exposure limits. Showers

Eyewash stations

Ventilation systems. Explosion-proof general and local exhaust ventilation.

## Individual protection measures, such as personal protective equipment

Eye/Face Protection

Wear goggles or chemical safety glasses. Refer to 29 CFR 1910.133 for eye and face

protection regulations.

Skin and Body Protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands. Complete suit protecting against chemicals, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace. Refer to 29 CFR 1910.138 for appropriate skin and body protection.

Respiratory Protection

If necessary, wear a MSHA/NIOSH-approved respirator. Refer to 29 CFR 1910.134 for

respiratory protection requirements.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and immediately after handling the product.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

## Information on basic physical and chemical properties

**BPN-008 - LINER SEALER** Revision Date: 19-DEC-2022

Physical state **Appearance** 

Liquid

Black high viscosity liquid

Odor

Petrolic

Color

Black

**Odor Threshold** 

Not determined

Property

Values

Not determined

Remarks • Method

pН

Melting point / freezing point

-90.0 to -90.1 °C / -131.7 to -130.3

°F

Boiling point / boiling range Flash point

98.1 to 98.7 °C 208.5 to 209.6 °F -4.0 °C / 24.8 °F

N-butyl acetate

**Evaporation Rate** Flammability (Solid, Gas)

Not determined

Not applicable

(Air=1)

Flammability Limit in Air

Upper flammability or explosive limits

Lower flammability or explosive

1.1%

limits Vapor Pressure

110.7 hPa (83.0 mmHg) at 37.7 °C (99.9°F), 53.3 hPa (40.0 mmHg) at

20.0 °C (68.0°F)

Vapor Density

3.30

0.684 g/mL at 25°C (77°F)

**Relative Density** 

Not determined

Water Solubility Solubility in other solvents **Partition Coefficient** 

Insoluble log Pow > 3,000 223.0 °C / 433.4 °F

Autoignition temperature Decomposition temperature Kinematic viscosity **Dynamic Viscosity Explosive Properties** 

Not determined Not determined Not determined Not determined Not determined

Other information

**Oxidizing Properties** 

Molecular weight 100.2 g/mol

## 10. STABILITY AND REACTIVITY

## Reactivity

Not reactive under normal conditions.

#### Chemical stability

Stable under recommended storage conditions.

## Possibility of hazardous reactions

None under normal processing.

## Conditions to Avoid

Heat, flames and sparks.

## Incompatible materials

Strong oxidizing agents.

## Hazardous decomposition products

None known based on information supplied.

## 11. TOXICOLOGICAL INFORMATION

## Information on likely routes of exposure

**Product Information** 

BPN-008 - LINER SEALER Revision Date: 19-DEC-2022

Eye Contact Avoid contact with eyes. May cause temporary irritation on eye contact.

Skin Contact Causes skin irritation. May be harmful in contact with skin.

Inhalation May cause drowsiness or dizziness. May cause irritation to the mucous membranes and

upper respiratory tract.

Ingestion May be fatal if swallowed and enters airways. May cause gastrointestinal irritation, nausea,

diarrhea, and vomiting.

## Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
N-Heptane 142-82-5	-	= 3000 mg/kg (Rabbit)	= 103 g/m <sup>3</sup> (Rat) 4 h

## Symptoms related to the physical, chemical and toxicological characteristics

Symptoms

Carcinogenicity

Please see section 4 of this SDS for symptoms.

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

Based on the information provided, this product does not contain any carcinogens or potential carcinogens as listed by OSHA, IARC or NTP.

STOT - single exposure May cause drowsiness or dizziness.

Aspiration hazard May be fatal if swallowed and enters airways.

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

Dermal LD50 3,333.00 mg/kg

ATEmix (inhalation-dust/mist) 114.00 mg/L

## 12. ECOLOGICAL INFORMATION

#### Ecotoxicity

Very toxic to aquatic life with long lasting effects.

## Component Information

Chemical name	Algae/aquatic plants	Fish	Crustacea
N-Heptane		375.0: 96 h Cichtid fish mg/L LC50	10: 24 h Daphnia magna mg/L
142-82-5			EC50

## Persistence/Degradability

Not determined.

## <u>Bioaccumulation</u>

There is no data for this product.

## Mobility

Chemical name	Partition coefficient
N-Heptane	4.66
142-82-5	

## Other Adverse Effects

## Not determined

## 13. DISPOSAL CONSIDERATIONS

## **Waste Treatment Methods**

**Disposal of Wastes** 

Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste disposal facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

Contaminated Packaging

Disposal should be in accordance with applicable regional, national and local laws and regulations.

## California Hazardous Waste Status

Chemical name	California Hazardous Waste Status
N-Heptane	Toxic
142-82-5	Ignitable

## 14. TRANSPORT INFORMATION

Note

Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.

DOT

**ÜN/ID** No

UN1133

**Proper Shipping Name** 

Adhesives

Hazard class

3

**Packing Group** 

II

IATA

**UN** number

UN1133

**Proper Shipping Name** 

Adhesives

Transport hazard class(es)

3

**Packing Group** 

H

IMDG

**UN** number

UN1133

**Proper Shipping Name** 

Adhesives

Transport hazard class(es)

**Packing Group** 

3

Marine Pollutant

11 Yes

## 15. REGULATORY INFORMATION

## International Inventories

Chemical name	TSCA	TSCA Inventory Status	DSL/NDSL	EINECS/ELI NCS	ENCS	IECSC	KECL	PICCS	AICS
N-Heptane	X	ACTIVE	X	X	Х	X	Х	X	X

**BPN-008 - LINER SEALER** 

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

## US Federal Regulations

## **CERCLA**

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355).

## **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Revision Date: 19-DEC-2022

## CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

## **US State Regulations**

#### California Proposition 65

This product does not contain any Proposition 65 chemicals.

## U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
N-Heptane 142-82-5	x	х	×
142-02-3	<u> </u>	22	

# 16. OTHER INFORMATION

NFPA Health Hazards Flammability Instability Special Hazards
1 3 0 Not determined
Health Hazards Flammability Physical hazards Personal Protection
1 3 0 Not determined

Issue Date: Revision Date:

09-Jun-2015 24-Jun-2020

Revision Note:

24-Jun-2020 New format

#### <u>Disclaimer</u>

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**