

A2024TI-DV-2010

CARS, LIGHT TRUCK TIRE CHANGERS

The market choice for reliability and long-lasting performance is designed for low-profile/ultra-high performance tires. Run-flat certified by all major tire manufacturers. PAX capable with accessory kit.

24''

Same features as the A2024TI

PLUS SP2000 SUPER POWER UNIT

+

PLUS PNEUMATIC BEAD PRESSING TOOL WITH SUPPORT (BPT)

- Pneumatic-powered upper disc holds bead into the wheel drop for mounting
- Designed for low-profile, EMT and high-performance tires and wheels
- Loosening upper bead for demounting
- Push down upper bead for lubrication and tire tool insertion
- Lowering upper bead for inspection between bead and demount head
- Lowering upper bead for inserting the bead clamp; this clamp makes it possible to lift the bead over the mount/demount head
- Shipping weight 815 lbs.
- BEAD PRESSING TOOL: Professional pneumatic devices for easy demounting and mounting operation of low-profile and Run Flat tires. Shipping weight 882 lbs.



A2024TI DV-SP2300



- **TAPERED ROLLER.** Facilitates demounting and mounting of first bead by keeping the bead within the rim well.
- The **LARGE DISC** lifts the tyre and detaches the lower bead.
- **ROTATING BEAD DEPRESSOR.**
- **WDK VERSION** with disc instead of roller.

SPECIFICATIONS

• working range	up to 26"
• maximum wheel height	14"
• press force on tools	1574 lbs
• compressed air	supply
• operating pressure	145 psi
• weight, standard version	117 lbs
• weight, WDK version	117 lbs

Same features as the A2024TI

PLUS SP2300

SUPER POWER UNIT

Universal multifunctional device for facilitating tyre mounting and demounting

The SP2300 is a practical and functional Helper device specifically designed to make mounting and demounting operations quicker, more precise and safer.

Two versions are available:

- SP2300 Standard, consisting of three integrated operating units capable of working on all types of tyre - including ultra low profile and run flat tyres - and light alloy wheel rims.
- SP2300 WDK, which differs from the standard version in having a bead depressor disc instead of a bead depressor roller.



OR



OPTIONAL ACCESSORIES

- Rim locked onto clamp with rim presser cone



A2024TI DV-SP300



SPECIFICATIONS

• working range	10" ÷ 24"
• maximum wheel height	13"
• press force on tools	1506 lbs
• operating pressure	102 psi
• weight, standard version	154 lbs
• weight, WDK version	154 lbs

Same features as the A2024TI

PLUS SP300

SUPER POWER UNIT

The SP 300 is a practical and functional Helper device specifically designed to make mounting and demounting operations quicker, more precise and safer.

Capable of working on all types of tyre - including ultra low profile and run flat tyres - and light alloy wheel rims.

- **TAPERED ROLLER**
- **MOBILE BEAD DEPRESSOR**
- **WHEEL PRESSER CONE**
- **LARGE DISC**

OPTIONAL ACCESSORIES

- Installation and customisation kit for SP300

