

Safety Data Sheet

Issue Date: 09-Jul-2015

Revision Date: 21-Jun-2016

Version 1

1. IDENTIFICATION

Product Identifier

Product Name Flammable Inner Liner Sealant Black, Flammable Repair Sealer Black

Other means of identification

SDS # ELG-008

Product Code Catalog Numbers: 1-746, 1-747, 1-739, 1-749, 2-746, 2-747, 2-739, 2-749, 4-746, 4-747, 4-739, 4-749, RS16K, CI10

UN/ID No UN1133

Recommended use of the chemical and restrictions on use

Recommended Use Rubber adhesive.

Details of the supplier of the safety data sheet

Supplier Address

ELGI Rubber Company, LLC
600 N. Magnolia Ave.
Luling, TX 78648
Ph: 830-875-5539

Emergency Telephone Number

Emergency Telephone (24 hr) INFOTRAC 1-352-323-3500 (International)
1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Appearance Black high viscosity liquid **Physical state** Liquid **Odor** Petrolic

Classification

| | |
|--|------------|
| Skin corrosion/irritation | Category 2 |
| Specific target organ toxicity (single exposure) | Category 3 |
| Aspiration toxicity | Category 1 |
| Flammable Liquids | Category 2 |

Hazards Not Otherwise Classified (HNOC)

May be harmful in contact with skin

Signal Word

Danger

Hazard statements

Causes skin irritation
May cause drowsiness or dizziness
May be fatal if swallowed and enters airways
Highly flammable liquid and vapor



Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling
Wear protective gloves/protective clothing/eye protection/face protection
Avoid breathing dust/fume/gas/mist/vapors/spray
Use only outdoors or in a well-ventilated area
Keep away from heat/sparks/open flames/hot surfaces. — No smoking
Keep container tightly closed
Ground/bond container and receiving equipment
Use explosion-proof equipment
Use only non-sparking tools
Take precautionary measures against static discharge
Keep cool

Precautionary Statements - Response

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
If skin irritation occurs: Get medical advice/attention
Wash contaminated clothing before reuse
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
Call a poison center or doctor/physician if you feel unwell
IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
Do not induce vomiting
IN CASE OF FIRE: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up
Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other hazards

Very toxic to aquatic life with long lasting effects

3. COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical Name | CAS No. | Weight-% |
|---------------|----------|----------|
| N-Heptane | 142-82-5 | 80-90 |

If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

First Aid Measures

| | |
|-----------------------|--|
| General Advice | Provide this SDS to medical personnel for treatment. |
| Eye Contact | Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. |
| Skin Contact | Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse. |
| Inhalation | Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell. If not breathing, give artificial respiration. |
| Ingestion | Do not induce vomiting. Immediately call a poison center or doctor/physician. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. |

Most important symptoms and effects

| | |
|-----------------|--|
| Symptoms | Causes skin irritation. May cause drowsiness or dizziness. May be harmful in contact with skin. May cause pulmonary edema. Possible symptoms are irritation of the mucous membranes, dry cough and respiratory difficulty. Other symptoms may include dizziness, headache, nausea, and loss of coordination. |
|-----------------|--|

Indication of any immediate medical attention and special treatment needed

| | |
|---------------------------|--|
| Notes to Physician | Treat symptomatically. Aspiration of material into the lungs due to vomiting can cause chemical pneumonitis which can be fatal. Epinephrine and other sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to high concentrations of hydrocarbon solvents. The use of other drugs with less arrhythmogenic potential should be considered. If sympathomimetic drugs are administered, observe for the development of cardiac arrhythmias. |
|---------------------------|--|

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Water spray (fog). Alcohol resistant foam. Dry chemical. Carbon dioxide (CO₂).

Unsuitable Extinguishing Media Do not use solid water streams.

Specific Hazards Arising from the Chemical

Highly flammable liquid and vapor. The liquid vapor may settle into low areas or may travel along the ground or surface to ignition sources where they might ignite or explode. Flash back possible over considerable distance.

Hazardous Combustion Products Carbon monoxide. Carbon dioxide (CO₂).

Explosion Data

Sensitivity to Static Discharge Take precautionary measures against static discharge.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use water spray to keep fire-exposed containers cool. Fight fire remotely due to the risk of explosion.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Wear protective clothing as described in Section 8 of this safety data sheet. Evacuate personnel to safe areas. Remove all sources of ignition. Ensure adequate ventilation. Avoid breathing vapors or mists.

Environmental precautions

Environmental precautions Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information.

Methods and material for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so. Prevent evaporation by covering with foam. Soak up and contain spill with an inert (i.e. vermiculite, dry sand or earth) absorbent material.

Methods for Clean-Up Use only non-sparking tools. Place in properly labeled, sealed, non-leaking containers. Dispose of contents/container via a licensed waste disposal contractor. For waste disposal, see section 13 of the SDS.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on Safe Handling Wash face, hands, and any exposed skin thoroughly after handling. Wear protective gloves/protective clothing and eye/face protection. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Ground/bond container and receiving equipment. Use spark-proof tools and explosion-proof equipment. Take precautionary measures against static discharges. Keep cool.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a cool, well-ventilated place. Store locked up. Heat sensitive-store under inert gas.

Incompatible Materials Strong oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

| Chemical Name | ACGIH TLV | OSHA PEL | NIOSH IDLH |
|-----------------------|-------------------------------|---|---|
| N-Heptane 142-82-5 | STEL: 500 ppm TWA: 400 ppm | TWA: 500 ppm TWA: 2000 mg/m ³ (vacated) TWA: 400 ppm (vacated) TWA: 1600 mg/m ³ (vacated) STEL: 500 ppm (vacated) STEL: 2000 mg/m ³ | IDLH: 750 ppm Ceiling: 440 ppm 15 min Ceiling: 1800 mg/m ³ 15 min TWA: 85 ppm TWA: 350 mg/m ³ |

Appropriate engineering controls

Engineering Controls Apply technical measures to comply with the occupational exposure limits. Showers
 Eyewash stations
 Ventilation systems. Explosion-proof general and local exhaust ventilation.

Individual protection measures, such as personal protective equipment

- Eye/Face Protection** Wear goggles or chemical safety glasses. Refer to 29 CFR 1910.133 for eye and face protection regulations.
- Skin and Body Protection** Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands. Complete suit protecting against chemicals, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace. Refer to 29 CFR 1910.138 for appropriate skin and body protection.
- Respiratory Protection** If necessary, wear a MSHA/NIOSH-approved respirator. Refer to 29 CFR 1910.134 for respiratory protection requirements.
- General Hygiene Considerations** Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and immediately after handling the product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

| | | | |
|-----------------------|-----------------------------|-----------------------|----------------|
| Physical state | Liquid | Odor | Petrolic |
| Appearance | Black high viscosity liquid | Odor Threshold | Not determined |
| Color | Black | | |

| <u>Property</u> | <u>Values</u> | <u>Remarks • Method</u> |
|-------------------------------------|--|-------------------------|
| pH | Not determined | |
| Melting Point/Freezing Point | -90.0 to -90.1 °C / -131.7 to -130.3 °F | |
| Boiling Point/Boiling Range | 98.1 to 98.7 °C 208.5 to 209.6 °F | |
| Flash Point | -4.0 °C / 24.8 °F | |
| Evaporation Rate | 4 | (butyl acetate = 1) |
| Flammability (Solid, Gas) | Not determined | |
| Flammability Limits in Air | | Not applicable |
| Upper Flammability Limits | 7% | |
| Lower Flammability Limit | 1.1% | |
| Vapor Pressure | 110.7 hPa (83.0 mmHg) at 37.7 ° C (99.9° F) , 53.3 hPa (40.0 mmHg) at 20.0 ° C (68.0° F) | |
| Vapor Density | 3.30 | (Air=1) |
| Relative Density | 0.684 g/mL at 25° C (77° F) | |
| Water Solubility | Not determined | |
| Solubility in other solvents | Insoluble | |
| Partition Coefficient | log Pow > 3.000 | |
| Auto-ignition Temperature | 223.0 °C / 433.4 °F | |
| Decomposition Temperature | Not determined | |
| Kinematic Viscosity | Not determined | |
| Dynamic Viscosity | Not determined | |
| Explosive Properties | Not determined | |
| Oxidizing Properties | Not determined | |

Other Information

| | |
|-------------------------|-------------|
| Molecular weight | 100.2 g/mol |
| VOC Content (%) | N/A |

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

Chemical Stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to Avoid

Heat, flames and sparks.

Incompatible Materials

Strong oxidizing agents.

Hazardous Decomposition Products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

- Eye Contact** Avoid contact with eyes. May cause temporary irritation on eye contact.
- Skin Contact** Causes skin irritation. May be harmful in contact with skin.
- Inhalation** May cause drowsiness or dizziness. May cause irritation to the mucous membranes and upper respiratory tract.
- Ingestion** May be fatal if swallowed and enters airways. May cause gastrointestinal irritation, nausea, diarrhea, and vomiting.

Component Information

| Chemical Name | ATEmix (oral) | ATEmix (dermal) | Inhalation LC50 |
|-----------------------|---------------|-------------------------|------------------------------------|
| N-Heptane 142-82-5 | - | = 3000 mg/kg (Rabbit) | = 103 g/m ³ (Rat) 4 h |

Information on physical, chemical and toxicological effects

- Symptoms** Please see section 4 of this SDS for symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

- Carcinogenicity** Based on the information provided, this product does not contain any carcinogens or potential carcinogens as listed by OSHA, IARC or NTP.
- STOT - single exposure** May cause drowsiness or dizziness.
- Aspiration hazard** May be fatal if swallowed and enters airways.

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document . mg/kg

ATEmix (dermal) 3,333.00 mg/kg

ATEmix (inhalation-dust/mist) 114.00 mg/L

12. ECOLOGICAL INFORMATION

Ecotoxicity

Very toxic to aquatic life with long lasting effects.

Component Information

| Chemical Name | Algae/aquatic plants | Fish | Crustacea |
|-----------------------|----------------------|------------------------------------|----------------------------------|
| N-Heptane 142-82-5 | | 375.0: 96 h Cichlid fish mg/L LC50 | 10: 24 h Daphnia magna mg/L EC50 |

Persistence/Degradability

Not determined.

Bioaccumulation

Not determined.

Mobility

| Chemical Name | Partition Coefficient |
|-----------------------|-----------------------|
| N-Heptane 142-82-5 | 4.66 |

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal of Wastes

Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste disposal facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

Contaminated Packaging

Disposal should be in accordance with applicable regional, national and local laws and regulations.

California Hazardous Waste Status

| Chemical Name | California Hazardous Waste Status |
|-----------------------|-----------------------------------|
| N-Heptane 142-82-5 | Toxic Ignitable |

14. TRANSPORT INFORMATION

Note Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.

DOT
UN/ID No UN1133
Proper Shipping Name Adhesives
Hazard Class 3
Packing Group II

IATA
UN/ID No UN1133
Proper Shipping Name Adhesives
Hazard Class 3
Packing Group II

IMDG
UN/ID No UN1133
Proper Shipping Name Adhesives
Hazard Class 3
Packing Group II
Marine Pollutant Yes

15. REGULATORY INFORMATION

International Inventories

| Chemical Name | TSCA | DSL/NDSL | EINECS/E LINC S | ENCS | IECSC | KECL | PICCS | AICS |
|---------------|------|----------|-----------------|---------|-------|---------|-------|------|
| N-Heptane | X | X | X | Present | X | Present | X | X |

Legend:

- TSCA* - United States Toxic Substances Control Act Section 8(b) Inventory
- DSL/NDSL* - Canadian Domestic Substances List/Non-Domestic Substances List
- EINECS/ELINC S* - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
- ENCS* - Japan Existing and New Chemical Substances
- IECSC* - China Inventory of Existing Chemical Substances
- KECL* - Korean Existing and Evaluated Chemical Substances
- PICCS* - Philippines Inventory of Chemicals and Chemical Substances
- AICS* - Australian Inventory of Chemical Substances

US Federal Regulations

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355).

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

| Chemical Name | New Jersey | Massachusetts | Pennsylvania |
|-----------------------|------------|---------------|--------------|
| N-Heptane 142-82-5 | X | X | X |

16. OTHER INFORMATION

| | | | | |
|--------------------|-----------------------|---------------------|-------------------------|----------------------------|
| <u>NFPA</u> | Health Hazards | Flammability | Instability | Special Hazards |
| | 1 | 3 | 0 | Not determined |
| <u>HMIS</u> | Health Hazards | Flammability | Physical hazards | Personal Protection |
| | 1 | 3 | 0 | Not determined |

Issue Date: 09-Jul-2015
 Revision Date: 21-Jun-2016
 Revision Note: New format

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet